

Compact Fans - AC



Compact Fans - AC



Model	Bearing	Voltage (VAC)	Frequency (Hz)	Current (A)	Speed (RPM)	Watt (W)	Air Flow (CFM)	Static Pressure (mm H ₂ O)	Noise (dBA)
-------	---------	---------------	----------------	-------------	-------------	----------	----------------	---------------------------------------	-------------

80X80X25mm

8A115HBAC	Ball	115	50/60	0.210/0.180	2300/2800	14/12	21/25	4/4.8	29/34
8A115HSAC	Sleeve	115	50/60	0.210/0.180	2300/2800	14/12	21/25	4/4.8	29/34
8A230HBAC	Ball	230	50/60	0.070/0.060	2300/2800	14/12	21/25	4/4.8	29/34
8A230HSAC	Sleeve	230	50/60	0.070/0.060	2300/2800	14/12	21/25	4/4.8	29/34

92X92X25mm

9A115HBAC	Ball	115	50/60	0.210/0.180	2300/2800	14/14	36/42	5/6	36/38
9A115HSAC	Sleeve	115	50/60	0.210/0.180	2300/2800	14/14	36/42	5/6	36/38
9A230HBAC	Ball	230	50/60	0.070/0.060	2300/2800	14/12	36/42	5/6	36/38
9A230HSAC	Sleeve	230	50/60	0.070/0.060	2300/2800	14/12	36/42	5/6	36/38

120X120X38mm

12A24HBAC	Ball	24	50/60	1/0.9	2650/2800	18/17	95/102	8.4/9.4	43/46
12A24HSAC	Sleeve	24	50/60	1/0.9	2650/2800	18/17	95/102	8.4/9.4	43/46
12A115HBAC	Ball	115	50/60	0.200/0.180	2650/2800	14/12	95/102	8.4/9.4	43/46
12A115HSAC	Sleeve	115	50/60	0.200/0.180	2650/2800	14/12	95/102	8.4/9.4	43/46
12A230HBAC	Ball	230	50/60	0.100/0.090	2650/2800	18/17	95/102	8.4/9.4	43/46

■ Ask for Low Noise versions

Specifications subject to change without notice

Compact Fans - AC



Model	Bearing	Voltage (VAC)	Frequency (Hz)	Current (A)	Speed (RPM)	Watt (W)	Air Flow (CFM)	Static Pressure (mm H ₂ O)	Noise (dBA)
-------	---------	---------------	----------------	-------------	-------------	----------	----------------	---------------------------------------	-------------

120X120X38mm

12A230HSAC	Sleeve	230	50/60	0.100/0.090	2650/2800	18/17	95/102	8.4/9.4	43/46
12A415HBAC	Ball	415	50/60	0.070/0.060	2650/2800	20/20	95/102	8.4/9.4	43/46
12A415HSAC	Sleeve	415	50/60	0.070/0.060	2650/2800	20/20	95/102	8.4/9.4	43/46

172Φx150x51mm & 172x172x55mm

17A115HBAC	Ball	115	50/60	0.450/0.450	2600/2750	41/38	190/235	16/21	52/55
17A115HSAC	Sleeve	115	50/60	0.450/0.450	2600/2750	41/38	190/235	16/21	52/55
17A230HBAC	Ball	230	50/60	0.250/0.245	2600/2750	38/37	190/235	16/21	52/55
17A230HSAC	Sleeve	230	50/60	0.250/0.245	2600/2750	38/37	190/235	16/21	52/55
17A415HBAC	Ball	415	50/60	0.125/0.125	2600/2750	38/38	190/235	16/21	52/55
17A415HSAC	Sleeve	415	50/60	0.125/0.125	2600/2750	38/38	190/235	16/21	52/55

220ΦX60mm & 220X220X60mm

22A115HBAC	Ball	115	50	0.640	2300	50	360	23	56
22A115HSAC	Sleeve	115	50	0.640	2300	50	360	23	56
22A115HBAC-X	Ball	115	50	0.650	2600	55	430	28	56

■ Ask for Low Noise versions

Specifications subject to change without notice

17A and 22A models available in square and round casings

Compact Fans - AC



Model	Bearing	Voltage (VAC)	Frequency (Hz)	Current (A)	Speed (RPM)	Watt (W)	Air Flow (CFM)	Static Pressure (mm H ₂ O)	Noise (dBA)
220ΦX60mm & 220X220X60mm									
22A115HBAC-X-6H	Ball	115	60	0.700	2600	55	430	28	56
22A230HBAC	Ball	230	50	0.320	2300	50	360	23	56
22A230HSAC	Sleeve	230	50	0.320	2300	50	360	23	56
22A230HSAC-X	Sleeve	230	50	0.32	2600	55	430	28	56
22A230HSAC-X-6H	Sleeve	230	60	0.40	2700	60	450	29	57
22A230HBAC-X	Ball	230	50	0.32	2600	55	430	28	56
22A230HBAC-X-6H	Ball	230	60	0.40	2700	60	450	29	57
22A415HBAC	Ball	415	50	0.200	2300	50	360	23	56
22A415HSAC	Sleeve	415	50	0.200	2300	50	360	23	56
22A415HSAC-X	Sleeve	415	50	0.160	2600	50	430	28	56
22A415HBAC-X	Ball	415	50	0.160	2600	50	430	28	56

■ Ask for Low Noise versions

Specifications subject to change without notice

17A and 22A models available in square and round casings